

## Direct Acting OHC Solid Bucket Follower Profiles

Master Number	Advertised Duration		Duration @ .050"		Cam Lift	
	IN	EX	IN	EX	IN	EX
430	229	244	181	195	0.206"/5.2mm	0.207"/5.2mm
438A	269	269	204	204	0.295"/7.5mm	0.295"/7.5mm
440B	271	271	207	207	0.365"/9.3mm	0.365"/9.3mm
407	266	266	210	210	0.376"/9.5mm	0.376"/9.5mm
404A	262	262	211	211	0.342"/8.7	0.342"/8.7
416	256	264	212	223	0.376"/9.5mm	0.376"/9.5mm
406	275	280	215	220	0.397"/10.0mm	0.399"/10.1mm
402B	250	250	216	216	0.379"/9.6mm	0.379"/9.6mm
405A	292	292	218	218	0.388"/9.8mm	0.388"/9.8mm
409	264	297	220	229	0.401"/10.2mm	0.421"/10.7mm
411A	270	270	220	220	0.312"/7.9mm	0.312"/7.9mm
446	270	279	222	212	0.402"/10.2mm	0.385"/9.8mm
408B	261	261	223	223	0.372"/9.4mm	0.372"/9.4mm
405B	280	280	224	224	0.396"/10.0mm	0.396"/10.0mm
421B	265	265	225	225	0.342"/8.6mm	0.342"/8.6mm
408A	291	291	226	226	0.370"/9.4mm	0.370"/9.4mm
433	292	281	228	219	0.454"/11.5mm	0.415"/10.5mm
404B	294	294	230	230	0.316"/8.0mm	0.316"/8.0mm
439	271	290	230	230	0.375"/9.5mm	0.375"/9.5mm
413A	279	279	232	232	0.360"/9.1mm	0.360"/9.1mm
402A	266	266	233	233	0.375"/9.5mm	0.375"/9.5mm
442A	269	269	233	233	0.373"/9.5mm	0.373"/9.5mm
442B	272	272	235	235	0.410"/10.4mm	0.410"/10.4mm

**Direct Acting OHC Solid Bucket Follower Profiles (continued)**

Grind No	Adv Dur @ .010"		Duration @ .050"		Cam Lift	
	IN	EX	IN	EX	IN	EX
403A	286	286	237	237	0.426	0.426
410B	290	290	238	238	0.341	0.341
420	289	286	238	237	0.429	0.429
445B	272	272	238	238	0.382	0.382
443	275	240	238	240	0.424	0.424
411B	310	310	239	239	0.469	0.469
418A	277	277	240	240	0.368	0.368
401A	293	293	242	242	0.372	0.372
434A	276	276	243	243	0.431	0.431
417	296	293	244	238	0.472	0.453
445A	280	280	247	247	0.447	0.447
400A	295	295	248	248	0.426	0.426
429	296	296	253	253	0.429	0.412
444B	290	290	254	254	0.447	0.447
400B	319	319	263	263	0.416	0.416
444A	300	300	264	264	0.447	0.447
432A	316	316	267	267	0.519	0.519
434B	328	328	270	270	0.441	0.441
418B	310	310	273	273	0.436	0.436