

Direct Acting OHC HYD Bucket Follower Profiles

Master Number	Advertised Duration		Duration @.050"		Cam Lift	
	IN	EX	IN	EX	IN	EX
415B	236	236	179	179	.260"/6.6mm	0.260"/6.6mm
427	227	240	189	200	0.317"/8.0mm	0.337"/8.0mm
438B	234	234	198	198	0.313"/7.9mm	0.313"/7.9mm
435B	236	236	200	200	0.350"/8.9mm	0.350"/8.9mm
414	235	243	202	211	0.203"/5.1mm	0.214"/5.4mm
415A	243	243	204	204	0.309"/7.8mm	0.309"/7.8mm
424B	256	256	205	205	0.334"/8.4mm	0.334"/8.4mm
422	237	229	209	198	0.406"/10.3mm	0.360"/9.1mm
424A	257	257	209	209	0.332"/8.4mm	0.332"/8.4mm
437A	241	241	209	209	0.372"/9.5mm	0.372"/9.5mm
428B	248	248	212	212	0.311"/7.9mm	0.311"/7.9mm
435A	250	250	215	215	0.380"/9.6mm	0.380"/9.6mm
440A	253	253	215	215	0.335"/8.5mm	0.335"/8.5mm
432B	260	260	219	219	0.362"/9.2mm	0.362"/9.2mm
423A	264	264	221	221	0.354"/9.0mm	0.354"/9.0mm
428A	254	254	221	221	0.400"/10.1mm	0.400"/10.1mm
436A	255	255	221	221	0.399"/10.1mm	0.399"/10.1mm
436B	260	260	225	225	0.394"/10.0mm	0.394"/10.0mm
426B	260	260	226	226	0.350"/8.9mm	0.350"/8.9mm
425	268	267	228	227	0.438"/11.1mm	0.438"/11.1mm
401B	266	266	232	232	0.345"/8.7mm	0.345"/8.7mm
419	272	272	236	236	0.448"/11.3mm	0.448"/11.3mm
426A	271	271	236	236	0.350"/8.9mm	0.350"/8.9mm