

Flat Tappet Solid Lifter Camshaft Profiles (.015" Valve Clearance)

Master Number	Advertised Duration @ .015"		Duration @ .050"		Duration @ .200"		Lobe Sep	Cam Lift	
	IN	EX	IN	EX	IN	EX		IN	EX
648	231	231	177	186	64	73	109	0.224	0.228
612	236	296	193	208	74	78	111	0.231	0.231
647	244	261	195	198	89	93	109	0.247	0.252
659	230	223	195	192	58	56	110	0.214	0.211
618	239	231	199	196	97	94	108	0.261	0.257
660	239	242	202	203	59	59	110	0.214	0.216
613	248	256	210	213	76	83	110	0.227	0.232
639	254	254	210	210	98	98	110	0.252	0.252
653	287	288	212	213	110	110	111	0.262	0.262
616	259	260	214	215	103	105	107	0.258	0.261
607	263	264	216	216	115	115	108	0.278	0.278
623	268	264	217	218	118	119	109	0.280	0.276
621	260	264	220	223	110	113	108	0.264	0.266
611	272	266	222	225	123	126	110	0.282	0.286
631	271	273	227	231	126	136	105	0.289	0.306
636	268	263	227	224	111	107	105	0.251	0.248
609	277	284	231	235	128	132	108	0.287	0.289
622	275	275	231	231	137	137	108	0.306	0.306
619	275	284	232	241	137	146	106	0.308	0.318
657	289	290	234	235	126	126	110	0.298	0.298
608	278	282	241	243	138	140	102	0.302	0.302
628	298	302	243	244	132	134	110	0.276	0.279
630	293	310	245	262	147	160	106	0.316	0.330
625	299	289	251	242	150	140	105	0.317	0.302
600	295	300	253	263	156	167	102	0.319	0.331