

Holden / Chev LS HYD Roller Profiles

Master Number	Advertised Duration @.006"		Duration @ .050"		Duration @ .200"		Lobe Sep	Cam Lift	
	IN	EX	IN	EX	IN	EX		IN	EX
49927LS	262	272	204	214	125	126	118	0.324	0.306
49908LS	264	274	210	219	125	132	113	0.311	0.311
49938LS	267	277	215	223	137	144	114	0.343	0.343
49915LS	268	268	216	216	141	140	112	0.353	0.347
49955LS	274	276	220	222	140	142	112	0.340	0.341
49925LS	277	277	221	221	137	137	112	0.325	0.325
49937LS	278	283	222	226	139	143	112	0.331	0.332
49920LS	275	275	224	224	143	143	112	0.341	0.341
49950LS	277	283	224	228	143	148	116	0.341	0.353
49951LS	283	289	224	231	142	148	114	0.359	0.359
49921LS	275	287	224	232	145	153	112	0.341	0.348
49919LS	275	287	224	232	145	153	114	0.341	0.348
49922LS	278	278	226	226	148	148	112	0.352	0.352
49939LS	278	286	226	232	149	154	113	0.358	0.355
49954LS	283	299	227	238	137	144	110	0.308	0.308
49953LS	282	287	228	234	143	151	114	0.334	0.337
49907LS	282	292	228	234	148	154	112	0.353	0.353
49940LS	282	290	230	237	143	159	110	0.362	0.362
49906LS	285	285	233	233	154	154	112	0.348	0.351
49933LS	293	303	237	248	158	161	112	0.360	0.360
49901LS	289	292	238	242	159	162	110	0.355	0.356
49934LS	292	302	238	246	158	164	112	0.360	0.365
49923LS	298	307	245	254	154	173	110	0.375	0.374
49942LS	297	303	246	252	168	173	114	0.364	0.364
49943LS	307	320	250	263	168	180	112	0.370	0.368

